

Media

Kaba security card C

Description

The security card C comes delivered with the Kaba standard configuration and the unique site key.

The unprogrammed version of the security card C is used in the Kaba Media Manager to create own applications and configurations.

The security card C is used for initialisation of CardLink or Card ID system MPVD.



Product numbers

KMID-SC004/options

Kaba security card C, Mifare

Versions

KMID-SC004

- Colour: black/silver

Order options

Options	
Version	
Standard	Security card C: with an access key and the Kaba standard configuration
unprogrammed	Security card C: without an access key and the Kaba standard configuration (Can be configured with Kaba Media Manager.)

Technical specifications

Environmental requirements	
Protection class	IP66
Temperature	-25 - 70 °C
Humidity	0 - 95 %rH, not condensing

Kaba security cards A and B

Description

Security cards A and B are contact smartcards (ISO 7816) and are required for generating customer-specific access system MPVD and their card configurations in Software Kaba Media Manager.

The generated site keys and card configurations are transferred to the site/system software using a security card C that has been generated by Kaba Media Manager.



Product numbers

KSEC-SA000

Kaba security card A, Mifare

KSEC-SB000

Kaba security card B, Mifare

KSEC-SET01

Kaba security cards SET, Mifare

Scope of supply

KSEC-SET01 with:

2 x KSEC-SA000

1 x KMID-SC004

The recommended security card set for Mifare system MPVD to be generated in Kaba Media Manager.

Versions

KSEC-SA000 and KSEC-SB000

- Colour: black/silver

Technical specifications

Environmental requirements	
Type	ISO 7816
Temperature	-25 - 70 °C
Humidity	0 - 95 %rH, not condensing